

GENERAL SPECIFICATIONS

SECTORMATIC MULTI-BLADE ROTARY SLICERS



SPECIFICATIONS	Model 400	Model 400WS	Model 500	Model 500WS
Maximum Output Capacity (Kg & Lbs / hour)	3000 / 6,600	6,600	3400 / 7,500	3400 / 7,500
Maximum Product Width (mm)	400	400	500	500
Maximum Product Height (mm)	140	140	140	140
Circular Blade Diameter (mm)	300	300	300	300
Power (kW)	3	5.5	3	5.5
Voltage Requirements	220/3ph	220/3ph	220/3ph	220/3ph
Machine Footprint: L x W (mm)	2,600 x 1130	2,600 x 1130	2,600 x 1230	2,600 x 1230
Machine Weight (kg)	500	560	510	570
FEATURES				
Bacteria Proof AISI 304 Stainless Steel Construction	Std	Std	Std	Std
Full Magnetic Safety & Security System	Std	Std	Std	Std
Low Voltage Electronic Controls	Std	Std	Std	Std
Infeed Conveyor	Std	Std	Std	Std
Outfeed Conveyor	Std	Std	Std	Std
Blade Set Extraction Stand	Std	Std	Std	Std
Stainless Steel Blade Set Protective Cover	Std	Std	Std	Std
“Plug N’ Play” Design	Std	Std	Std	Std
“60 Second” Blade Set Changeover	Std	Std	Std	Std
Locking Wheel System	Std	Std	Std	Std
No Tool Requirement For Inspection Or Cleaning	Std	Std	Std	Std
Automatic Ozonization System	Std	Std	Std	Std
Blade Pulsing	Std	Std	Std	Std
Automatic Washing System <ul style="list-style-type: none"> • 3 Cleaning Programs • Separate High Pressure Water Gun • 5 Liters of Detergent 	Opt	Std	Opt	Std
Additional Blade Sets <ul style="list-style-type: none"> • From 6mm to 48mm • With Stainless Steel Blade Set Protective Cover 	Opt	Opt	Opt	Opt
Blade Set Extraction Stand For Additional Blade Set(s)	Opt	Opt	Opt	Opt
Vertical Infeed Conveyor System	Opt	Opt	Opt	Opt
Butterfly Blade Sets	Opt	Opt	Opt	Opt
Adjustable Product Side Guide	Opt	Opt	Opt	Opt